AWCL-300-6P-Audio 3 channels audio synchronized **RGB** Controller

Data Sheet





TEL: +886-2-29582427 FAX: +886-2-29582437

1. Features

- Support IR-remote control interface ∘
- R \ G \ B brightness can be adjusted individually, and auto-save the setting \circ
- Built-in six LED dynamic programs; dynamic mode can be set Fade/Jump and changed the dynamic speed.
- Real Audio Synchronized color LED Control.
- Automatically control mode switched between Audio Synchronized modes with Silent color fade mode.
- Adjustable Sensitivity for audio synchronized mode (including Microphone and Line-in sources).
- Audio source option for Line-in or Microphone.
- The maximum output is 4A x 3 channels, that is 150W/12V or 300W/24V or

2. Specifications

Operation Voltage	DC10V~30V ·
LED Output Power	150W/12V or 300W/24V
LED Module Type	Constant Voltage with constant current or
	Constant voltage with limit voltage.
Max output current	4A/channel x 3 channel
Weight	250g
Size	L:110mmxW:70mmxH:23mm
Operation Temperature	0°C ~+70 °C
Storage Temperature	-20°C ~ +85 °C







Output power: DC24V/300W; DC12V/150W

Alphawave Photonics Corp.

1F, No.283, Chang-an Street, Banciao City, Taipei County, Taiwan http://www.awled.com

TEL: +886-2-29582427 FAX: +886-2-29582437